



FTS 32

EVANESCENT OIL

PRESSING, FOLDING, FORMING, etc.

DEFINITION

Evanescent (evaporating) oil for metal work: deformation, forming, folding and cutting medium and thin sheet metal.

ADVANTAGES

- Does not stain metal
- Can be used for a variety of medium-sized operations: forming and cutting.
- Provides excellent anti-corrosion protection.
- Possesses considerable quenching ability.
- Improves the rate of zero-defect production.
- Can be used for working a variety of metals: ferrous and non-ferrous, aluminium, copper, cast iron, stainless steel and other alloys.
- Economical thanks to its effectiveness in a wide variety of situations.

APPLICATION FIELDS

- Folding, cutting, bending, stamping, profiling, rolling, etc.
- Manufacture of non-food packaging, such as tubs, tins, etc.
- Manufacture of buckets, aerosoles, burettes, etc.
- Manufacture of air conditioning fins, vehicle parts, etc.
- Also ideal for many industrial applications.

TECHNICAL CHARACTERISTICS

Colour	colourless
Density at 25°C - ASTM D 4052	0.80
Kinematic viscosity at 40°C - ASTM D 445	1.5 mPa.s
Flash point - ASTM D 56	> 61°C

INSTRUCTIONS FOR USE

- Ready to use.
- The evanescent lubricant can be applied drop by drop, by spraying or using felt.

PACKAGING

5 l Jerrican	ref. 2874 J1	x 1
20 l drum	ref. 2874 O1	x 1
200 l drum	ref. 2874 U2	x 1