



ORATEN

LUBRICANT and MOULD RELEASER

SILICONE-FREE

Ideal for plastics

DEFINITION

Lubricant for mould releasing, anti-adhesion and lubrication.
Guaranteed silicone-free meaning it can be used to clean up after painting, screen printing, and collage projects.

ADVANTAGES

- Does not leave stains, rings, or rubbery residue.
- Does not bond.
- Apply thin layers for maximum efficiency.
- Excellent water-repellent properties.
- Protects moulds against corrosion,

APPLICATION FIELDS

Demoulding polyamides, polyesters, PU, epoxies, rubber, ABS etc.
Lubricate metal-metal, metal-plastic, wood-metal assemblies, etc.
Can be used in the plastic industry because of the product's numerous characteristics.

TECHNICAL CHARACTERISTICS

Aspect transparent liquid
Colour colourless
Operating temperature..... -30°C to +200°C

INSTRUCTIONS FOR USE

Spray an even and thin layer onto the parts to be treated and repeat the operation if necessary.

PACKAGING

Aerosol 650 ml	Ref. 4811 A4	x 12
5 litre container	Ref. 2811 J1	x 4

1/1
Head office

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE
Tel. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 www.orapi-maintenance.com