



# **REDUCE 4**

## **SUPER DE-SEIZING**

**CLEANS - DE-SEIZES - LUBRICATES**  
**WATER-RESISTANT and ANTI-CORROSIVE**

### **DEFINITION**

Quick action, super-penetrating de-seizer and rust reducer that provides a phosphate coating.

### **ADVANTAGES**

- Works very quickly.
- Wets, penetrates, cleans and lubricates in one single step.
- Enables very difficult de-seizing without damaging threads.
- Provides a water-repellent and phosphate coating.
- Contains no silicone.
- Possesses anti-rust, anti-corrosion (creates a corrosion-inhibitive film) and reinforced anti-wear properties.

### **APPLICATION FIELDS**

REDUCE 4 is particularly suited for loosening assemblies that are very seized: bolts, nuts, screws, threads, waterworks rods, pulleys and mountings requiring usage of an effective de-seizer. REDUCE 4 then produces a phosphate coating on parts, and lubricates very well over several months. REDUCE 4 provides perfect resistance to water and effective and long-lasting protection regardless of environmental humidity levels surrounding treated parts.

### **TECHNICAL CHARACTERISTICS**

Aspect .....	Transparent liquid
Odour .....	Light
Density at 20°C .....	0.825
Flash point .....	>60°C

### **INSTRUCTIONS FOR USE**

**1/2**

**Manufacturing site and registered office**

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE

Tél. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 - [www.orapi-maintenance.com](http://www.orapi-maintenance.com)

ORAPI ® cannot be expected to know all applications in which its products are used or their conditions of use. ORAPI ® shall not be held responsible: for the suitability of its products for a given use or specific purpose, for the methods of application over which it has no control. The information contained in this technical data sheet can on no account be a substitute for the preliminary tests which are essential and which must be carried out in order to check the suitability of the product to each intended application. The user of the product described in this technical data sheet is solely responsible for all measures required to protect people and property from hazards that may arise from the implementation and/or use of this product. Therefore, ORAPI ® renounces any implicit or explicit guarantees, including guarantees relating to marketability or suitability for a certain purpose, resulting from the sale or use of its products. In particular, ORAPI ® renounces any claims for incidental or consequential damages whatsoever, including financial operating losses..

Apply generously to parts to be loosened.  
Wait for the product to settle between surfaces.  
Release parts.

## PACKAGING

---

270 ml aerosol	ref. 4800 A8	x 12
405 ml aerosol	ref. 4800 A2	x 12
800 ml aerosol	ref. 4800 A5	x 12
500 ml spray bottle	ref. 2800 i1	x 12
1 liter metal jerry-can	ref. 2800 i2	x 6
5 L jerry-can	ref. 2800 J1	x 4
200 L drum	ref. 2800 U2	x 1

## HOMOLOGATION

---

**AIMS 09-00-002** airbus – british aerospace  
**BOEING D6-17487 R**

Délivré le 05 mars 2014 par SMI – Miami – USA  
SMI ref 1312/265



Reference numbers:

NATO Defense XS 66 - AIR DCSEA 604/1 - US MIL G 234 111

SNECMA 90358249680

**2/2**

**Manufacturing site and registered office**

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE

Tél. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 - [www.orapi-maintenance.com](http://www.orapi-maintenance.com)