



SR 05

PROTECTIVE VARNISH

DEFINITION

Long-lasting, scratch-resistant varnish that leaves a hard film and protects from corrosion during storage; cold application.

ADVANTAGES

VERNIS SR 05 is a long-lasting product to protect against corrosion; can be applied on all clean metal frames.

The applied product sets with the evaporation of the solvent.

The film is waterproof and impermeable to aggressive, corrosive agents, and the elements.

Aerosol packaging enables easy and even application on surfaces.

Bulk packaging can be used in a bath, with a sprayer or with a brush.

The varnish covers the part to be treated perfectly and dries quickly.

Contains no chlorinated solvents.

The film can be removed with ORAPI 507-NDI.

Bonds perfectly with all metals.

Resists mineral and synthetic oils extremely well.

Dry film withstands up to 160°C.

APPLICATION FIELDS

Protection of extrusion sub-presses, moulds used in the glassworks and plastics industries, for indoor and outdoor storage.

Protection of all mechanical parts that must be stored or packaged before delivery.

TECHNICAL CHARACTERISTICS

Aspect Transparent liquid
Colour Red
Salt Spray Test >250 h

1/2

Manufacturing site and registered office

Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres - 01150 Saint-Vulbas - FRANCE

Tél. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26 - www.orapi-maintenance.com

ORAPI® cannot be expected to know all applications in which its products are used or their conditions of use. ORAPI® shall not be held responsible: for the suitability of its products for a given use or specific purpose, for the methods of application over which it has no control. The information contained in this technical data sheet can on no account be a substitute for the preliminary tests which are essential and which must be carried out in order to check the suitability of the product to each intended application. The user of the product described in this technical data sheet is solely responsible for all measures required to protect people and property from hazards that may arise from the implementation and/or use of this product. Therefore, ORAPI® renounces any implicit or explicit guarantees, including guarantees relating to marketability or suitability for a certain purpose, resulting from the sale or use of its products. In particular, ORAPI® renounces any claims for incidental or consequential damages whatsoever, including financial operating losses.

TECHNICAL CHARACTERISTICS - continued

VERNIS SR05 bulk

Density at 20°C	0.89 g/cm ³ ±0.05
Film dried to dust-free and dry to handle level	5 min
Durability of treatment	1 year under normal conditions, indoors / 6 months outdoors
Coverage	20 m ² /L for 10 microns thickness
Non-volatile matter	23% ±1 in weight
Flash point	< 4°C

VERNIS SR05 aerosol

Volume	650 ml gross / 500 ml net
Coverage	5 m ² /aerosol
Coating thickness per layer	15 microns

INSTRUCTIONS FOR USE

Aerosol: Spray a thin layer over the surface to be treated. If necessary, to achieve a thicker coating, spray on a second coat after the first coat is dry.

Bulk: Coat the parts to be treated by spraying, painting or soaking. Allow to dry before handling.

PACKAGING

650 ml aerosol	Ref. 4714 A4	x 12
5 L jerry-can	Ref. 2714 J1	x 4

AUTHORISATION

- Aérospatiale Reference PQ 81600: NATO C 632